

BED FRAMES LOW BED 500



LOW BED 500

The LOW BED 500 low beds features a travel range of 7 7/8" to 30" and offers a large range of configurations in a state of the art platform.



Key Product Features


- 7 7/8" low to 30" high
- Mobile or locked at any height
- Travels virtually straight up and down
- Variety of options and accessories
- Choice of head and footboard designs and finishes
- Choice of side and assist rails
- Choice of extenders
- Baseboard bumper and corner mattress stops



BED FRAMES LOW BED 500




REMOTE CONTROL AND SETTINGS



***Collapsible
3/4 length side
rails***



***1/2 length head
end side rails***



***3 position
assist rail***



***Fixed assist
rail***

Certifications

- Certified to UL/CSA standards

Electrical Specifications

- **Electric Motors:** Four (4) DC self lubricating Linear Actuators.
- **Voltage:** 110 Volts
- **Hertz:** 60 Hz
- **Rated Amps:** 3.5 Amp Max
- **Cord Type / Length:** 2.5 Meters minimum 3 prong.
- **Emergency Power back-up battery Pack:** Optional. 24 Volt.

Mechanical Specifications

Length including bumper	88 3/4"
Length (deck)	80"
Width (deck)	35"
Deck Height – Low	7 7/8"
Deck Height – high	30"
Deck Angles	
- Head elevation	0 – 70 degree
- Knee elevation	0 – 20 degrees
Safe Working Load*	500 lbs

* Includes resident, mattress, head and foot board and accessories.