



FEATURES

CT

- Full body lateral rotation
- Variable rotation cycle times from 3 to 90 minutes
- Low Pressure / Power Failure audible and visual alarms
- 3 modes of therapy
 - Static Low-Air-Loss
 - Pulsating Low-Air-Loss
 - Continuous Lateral Rotation (with Low-Air-Loss)
- Fowler feature for seat inflation when head is elevated
- Lockout to eliminate unintentional setting change
- Turn & Hold Feature

PRESSURE STUDY

ABCDEFGHIJKLMNOPQRSTUVWXYZ

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31



Sensors included 1088
Average pressure 4.50
Maximum pressure 33.52
Center of pressure 12.8, 33.20
Patient info.
Sex: female Height: 5'4" Weight: 215 lbs.

The AME4700ROT combines True Low-Air-Loss with Full Body Lateral Rotation capabilities in a complete mattress replacement system.

The microprocessor controlled blower unit features up to a 40° "Full Turn", and "Right Turn" modes of rotation. These rotation modes have a minimum cycle time of 3 minutes and a maximum of 90 minutes. The "Turn & Hold" feature allows the caregiver to rotate the patient to the left or right to help administer the patient. Additional features include: "Static" for stationary low air loss therapy, "Fowler" to boost seat inflation when the head is elevated, "Auto Firm" for rapid inflation and easy patient transfer, "Lockout" to maintain caregiver settings without accidental interruptions, "Low Pressure" and "Power Failure" audible / visual alarms, and "Self Diagnostic Check" to quickly assess all switches and sensors for proper calibration and operation.

The **The AME4700ROT** is a domestic mattress with 20 interchangeable air cells that are incorporated with a side support bolster which cradles the patient when rotating. The entire system is contained in a durable woven base, and the polyurethane coated top cover is waterproof yet highly vapor permeable. The entire system is portable and fits most standard medical bed frames.



control unit detail



side bolster



SPECS

Control Unit

Dimensions: 16"L x 6"W x 10.5"H
Weight: 11 lbs.
Cycle Time: Variable (3-20, 30, 45, 60, 75, 90 minutes)
Electrical Rating: 120V/60Hz
Power Cord: Harmonized Hospital Grade Plug
Warranty: 1Year

Support Surface

Weight Capacity: 350 lbs.
Inflated Dimensions: 35"W x 80"L x 8"H
Warranty: 2 Year Limited
Top Cover Warranty: 90 Days